



Specifications :

Power (W)	70-150
Voltage (V)/ Frequency (Hz)	230/50
Power factor	0,9
Lamp holder	E27/ E40
Support height (m)	5-9
Weight (kg)	4,3
Protection degree	IP66/IK08

Compliance: EN 60598, EN 60529 et EN 62262.

Optical type: « cut off » in accordance with the strictest laws for luminous pollution.

Maintenance: Easy maintenance and access to the equipment plate and the lamp.

Packing: Unique in a carton box

Model: *PLAY I*

Reference: *PLI150*

Lamps: *HPS 70 ~ 150W*

Technical characteristics:

Aluminum housing molded under high pressure
Paint in polyester powder after chrome treatment.

Pure and anodized aluminum reflector
Transparent, heat and mechanical stress resistance tempered glass (Available also with flat glass or cambered glass).

Stainless steel bolts and clips.
Adjustable galvanized steel lamp holder bracket.
Silicone sealing expended anti-aging, adopted to compensate operating expansions.

One block white porcelain lamp holder.
Integrated cable supply in a packing, adapted for cables ϕ 10 – 14 mm.

The supply unit includes the magnetic ballast with thermal protection if necessary, the ignitor adapted according to the lamp and the capacitor.

Internal electrical compartment in the reflector back part.

Fixation system on the support head with spigot ϕ 50 mm or ϕ 60 mm

N.B: On request, possibility to provide double regime ballast 150 W.