



Specifications :

Power (W)	150-400
Voltage (V)/ Frequency (Hz)	230/50
Power factor	0,9
Lamp holder	E40
Height (m)	7-12
Weight (kg)	5,8
Protection degree	IP66/IK08

Compliance : EN 60598, EN 60529 and EN 62262.

Optical type: « cut off » in accordance to the strictest laws for luminous pollution.

Maintenance: Easy access and maintenance to the Equipment plate and the lamp.

Packing: Unique in a carton box.

Model: *PLAY III*

Reference: *PLIII400*

Lamps: *HPS 150 ~ 400W*

Technical characteristics:

Aluminum housing molded under high pressure

Paint in polyester powder after chrome treatment.

Pure and anodized aluminum reflector

Transparent, heat and mechanical stress resistance tempered glass (Available also with flat glass or cambered glass).

Stainless steel screws and clips

Adjustable galvanized steel lamp holder bracket.

Silicone gasket expended anti-aging, adopted to compensate operating expansions.

One bloc white porcelain lamp holder

Integrated supply cable in a packing, adapted for cables ϕ 10 – 14 mm.

The supply unit includes the magnetic ballast with thermal protection if necessary, the ignitor adapted according to the lamp and the capacitor.

Internal electrical compartment in the reflector back part.

Fixation system on the support head with spigot ϕ 50 mm or ϕ 60 mm

N.B: On request, possibility to provide double regime ballast 250 W.